

PRODUCT DOCUMENTATION from FORESTIA AS

Product: Forestia Walls2Paint	September 2018
Supplier	FORESTIA AS
Address	N-2435 Braskereidfoss
Phone	+47 62 42 82 00
Mail	forestia.kundesenter@byggma.no
Contact person	Vegard Grønnerud

Dimension	Boards pr pallet <i>stk</i>	Net area per board <i>m²</i>	Weight per pallet <i>kg</i>
12x0620x2390	50	1,43	685
12x0620x2600	50	1,56	744

Quality Assurance: Forestia`s particleboard manufacturing plants are certified in accordance with NS-EN ISO 9001. The product is CE-marked. Altogether, this ensures high and consistent quality.

Product description	12mm thick particleboard with wallpaper and locking profile, ready to be painted.
Field of use	Walls in dry rooms, indoor, climate class 1.
Wallpaper	Glass fiber-based
Colour	White
Maintenance	Mild soapy water
Type of treatment	Must be painted. We recommend use of well known interior paint (acrylic paint). Paint twice.
Components	Particleboard: approx. 84 % wood particles, approx. 9 % UF-glue with cas.nr 9011-11-6, approx. 7 % water. Foil: Wallvision 27 Surface Liner FD1275. Foil glue: Dynea Prefere 4108 Product documentation can be supplied.

Product characteristics	
Density	Approx. 715 kg/m ³
Thermal conductivity	$\lambda_p = 0,13 \text{ W/mK}$
Fire resistance	D-s2, d0
Moisture resistance	Field of use : Climate class 1 (NS-EN 1995-1-1, Eurocode 5).
Formaldehyd class	Class E1, the board contains less than 8mg per 100g particleboard.
Durability	Lifetime of entire house.
Environment	Is made from virgin wood, free from PCBs. Formaldehyde emission in accordance with the most stringent class of the current European standard. Manufactured in a factory certified in accordance with NS-EN ISO 14001/@FSC/PEFC.
Storage at the construction site	Dry storing indoors in unopened packaging. For outdoor storage see installation instructions.
Handling	With care, so that foil and profile are not damaged
References	Instructions for use, and brochure.