

PDS – Product Data Sheet - FORESTIA AS

Product: Forestia Walls4You	January 2018
Supplier	FORESTIA AS
Address	N-2435 Braskereidfoss
Phone	+47 38 13 71 00
Mail	forestia.kundesenter@byggma.no
Contact person	Vegard Grønnerud

Dimension	Boards per packet	Boards per pallet	Net area per board <i>m²</i>	Weight per pallet <i>kg</i>
12x0620x2390mm	2	30	1,43	448

Quality Assurance: Forestia`s particleboard manufacturing plant are certified in accordance with NS-EN ISO 9001. The product is CE-marked. Altogether, this ensures high and consistent quality.

Product description	12mm thick particleboard with wallpaper and locking profile
Field of use	Walls in dry rooms, indoor, climate class 1.
Components	Approx. 84 % wood particles, approx. 9 % UF-glue with cas.nr. 9011-11-6, approx. 7 % water.
Maintenance	Mild soapy water

Product characteristics	
Density	P4-quality: 715 kg/m ³
Thermal conductivity	$\lambda_p = 0,13$ W/mK
Fire resistance	D-s2, d0.
Moisture resistance	Field of use: Climate class 1 (NS-EN 1995-1-1, Eurocode 5).
Formaldehyd class	Class E1, the board contains less than 8mg per 100g particleboard.
Durability	Lifetime of entire house.
Environment	The product is made from virgin wood, free from PCBs. Formaldehyde emission in accordance with the most stringent class of the current European standard. Manufactured in a factory certified in accordance with NS-EN ISO 14001/PEFC and ®FSC. (FSC-C124500).
Storage at the construction site	Dry storing indoors in unopened packaging. For outdoor storage, see installation instructions.
Handling	With care so the foil and profile stays intact.
References	Instruction for use, and brochure.