

PDS - Product Data Sheet - FORESTIA AS

Product: Forestia eliteX				August 2020
Supplier				FORESTIA AS
Address				N-2435 Braskereidfoss
Phone				+47 38 13 71 00
Email				forestia.kundesenter@byggma.no
Contact				Vegard Grønnerud
Dimention	Plates per pallet	Plates per. packet	Net area per plate <i>m</i> ²	Weight per pallet <i>kg</i>
Wall boards:				
12x0620x2390 – Grey Slate	48	2	1,43	679
12x0620x2390 – Grey Sand	48	2	1,43	679
12x0620x2390 - White	48	2	1,43	679
12x0620x2440 - White	48	2	1,46	693
12x0620x2600 - White	48	2	1,56	738
12x0620x3000 - White	48	2	1,80	854
Ceiling boards:				
12x0620x1220 - White	50		0,72	345

Quality Assurance: Forestia`s particleboard manufacturing plant is certified in accordance with NS-EN ISO 9001. The product is CE-marked. Altogether, this ensures high and consistent quality.

Product description Melaminecovered P7 board to be used in humid conditions. For walls and ceilings.

Point of use Can be used as boards for walls and ceiling in humid conditions in for example barns and laundry rooms.

Foil Melamine

Maintenance Can be washed with all non-greasy detergents

Content:

Particleboard: approx. 80 % wood particles, approx. 13 % UF-glue with cas.nr 9011-05-6/MUF-glue with cas. Nr 25036-13-9, approx. 7 % water.

Foil: Melamine

Product characteristics

Product class P7

Density Ca. 750 kg/m³

Thermal conductivity $\lambda_p = 0,15$ W/Mk

Fire resistance D-s1, d0.

Moisture resistance Area of use = Climat class 2 (NS-EN 1995-1-1, Eurocode 5).

Formaldehyde content Class E1 (≤ 8 mg pr 100g oven dry board)

Sound Goes under the term sound radiation reducing plate. Has sound technical characteristics similar to comparable plate types (plaster, wood fiber) and formats.

Environment The product is made from virgin wood, free from PCBs. Formaldehyde emissions in accordance with the strictest class of the current European standard. Manufactured in a factory certified in accordance with NS-EN ISO 14001 / PEFC and @FSC. (FSC-C124500).

Storing Primarily dry storing indoors in unopened packaging. For outdoor storage see installation guide.

Handling Gentle, so that the surface and profile are not damaged. The plates are to be lifted from the packages.

Accessories See pricelist.

References Instruction for use, and brochure.