DECLARATION of PERFORMANCE.

Ref. no.: YT-03.

1. Product name: 12 mm Forestia One Step for Walls.

2. Product type: Particleboard type: NS-EN 312 P2

3. Intended use: **Boards for interior fitments (including furniture)**

for use in dry conditions.

4. Manufacturer: Forestia AS, 2435 Braskereidfoss, Norway.

5. System of attestation of conformity: **System 4**

6. Harmonised standard: **NS-EN 13986:2004+A1:2015**.

7. Declared performance:

| Essential chatacteristics: | Performance: | Harmonised technical spesification: |
|---|--------------|-------------------------------------|
| Bending strength | 11 MPa | |
| Modulus of elasticity | 1800 MPa | |
| Internal bond | 0,40 MPa | |
| Reaction to fire: | | |
| 12 mm particleboard, density $> 600 \text{ kg/m}^3$: | D-s2,d0 | |
| Formaldehyde class | E1 | |
| Airborne sound insulation | NPD | NS-EN |
| Sound absorption: | | 13986:2004+A1:2015. |
| -Frequency range 250 – 500 Hz | 0,10 | |
| -Frequency range $1000 - 2000 \text{ Hz}$ | 0,25 | |
| Water vapor permeability µ, wet/dry cup | 15 / 50 | |
| Thermal conductivity λ | 0,13 W/(m K) | |
| Biological durability | NPD | |
| Release of pentachlorphenol | < 5 ppm | |

NPD = No performance declared

8. The performance of the product identified in points no. 1 and 2 are in conformity with the declared performance in point no. 7.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point no. 4.

Signed for and on behalf of Forestia AS by:

Vegard Grønnerud, Quality Manager

Name Function.

Braskereidfoss, 14.09.2022

Signature